

Product Code: TDM 3000 HD

-
- TDM 300 HD DSB Modulator
- TECHNOLOGY TDM 3000 HD 1 Channel (Dual Side Band) Modulator
- MCU controlled PLL
- High accuracy and stability of video carrier and audio subcarrier
- Audio subcarrier selectable: 5.5MHz、6.0MHz、6.5MHz
- With RF loop input and auto storage at power outage
- LED channel number display
- Double side band modulation for non-adjacent usage
- Output level adjustable

HDMI signal to RF Modulator

Features:

- Features:
- MCU controlled PLL,
- High accuracy and stability of video carrier and audio subcarrier,
- Audio subcarrier selectable: 5.5MHz、6.0MHz、6.5MHz,
- With RF loop input and auto storage at power outage,
- LED channel number display,
- Double side band modulation for non-adjacent usage,
- Output level adjustable,

Specifications

Item	Specification	Item	Specification
Frequency range	47~870MHz	Input Resolution	640*480@60Hz 480i, 480p, 576i, 576p, 720p, 1080i, 1080p@50Hz/60Hz
Output Level	90dBμV		
A/V Ratio	-15±2dB	HDMI Version	HDMI 1.3
Visual Carrier Freq. Accuracy	±5KHz	HDCP Version	HDCP 1.3
Output Return Loss	14dB	Output Impedance	75Ω
Spurious Rejection	50dB	Input Voltage	100-240V~50-60Hz