

TPT 17x4 RACK TYPE



- TPT17X4 ACTIVE TAP OFF
- TAP OFF ACTIVE

| | TPT10X4 | TPT14X4 | TPT17X4 |
|--------------------------------|--------------|--------------|---------------|
| Frequency operation range SAT | 950-2150Mhz | 950-2150Mhz | 950-2150Mhz |
| Frequency operation range TERR | 47-870Mhz | 47-870Mhz | 47-870Mhz |
| SAT + TERR in | 9+1 | 13+1 | 16+1 |
| SAT + TERR out | 10X4 | 14X4 | 17X4 |
| SAT Gain | +5dB±1 | +5dB±1 | +5dB±1 |
| TERR Gain | -7dB±1 | -7dB±1 | -7dB±1 |
| SAT-SAT Isolation | >31dB | >31dB | >31dB |
| SAT-TERR Isolation | >50dB | >50dB | >50dB |
| Max. signal out SAT | 100dBµV | 100dBµV | 100dBµV |
| Operation voltage | 18V 1,5A | 18V 1,5A | 18V 2A |
| Total current | 130mA | 160mA | 200mA |
| Operation temperature | -20...+ 50C° | -20...+ 50C° | -20...+ 50C° |
| Dimensions | 345x152x50mm | 290x154x52mm | 180x485x415mm |
| Weight | 660gr | 870gr | 1600gr |

| | | | |
|-------|--|--|---------|
| Desi: | | | 12.0765 |
|-------|--|--|---------|